

TTP-81

Chemical nature	Water dispersion of polyurethane
Appearance	Liquid
Solids content	20 \pm 1%
pH	9,0 - 10,0
Ionicity	Anionic

Applicazioni

TTP-81 è un poliuretano alifatico in dispersione acquosa con alto grado di lucido, asciutto di media morbidezza. Trova impiego soprattutto su pelli arredamento e pelletteria per applicazioni finali in rifiniture completamente acquose ad alte tenute e solidità. Il grado di lucido può essere regolato con l'aggiunta del TWC 1507 avente le stesse peculiarità.

Main applications

TTP-81 is a water dispersion of aliphatic polyurethane and it forms very gloss, dry and medium-soft films. It is suitable for water-borne finishing of furniture and leather goods articles with high fastness. Its high gloss can be tuned by adding some amounts of TWC 1507, which has the same high fastness features.

KEEP FROM FREEZING; CAN BE STORE FOR 6 MONTHS BETWEEN +5 AND +35°C.

Our application recommendation are in line with our present state of knowledge and they do not exempt the customer from performing his own tests to determine the suitability of the supplied products for the intended purposes. Application of the products lies outside the scope of our control and therefore comes within the customer's sphere or responsibility. We guarantee the satisfactory quality of our products subject to general terms of sale and delivery.