



**AUSILIARI  
CHIMICI**

## TWC-1503 MATT

Chemical nature	Water dispersion of polyurethanes
Appearance	White liquid
Solids content	16 $\pm$ 1 %
pH	7,0 – 9,0
Ionicity	Anionic

### Applicazioni

TWC-1503 MATT è un appretto finale opaco pronto all' uso, forma films morbidi ed opachi. Permette di ottenere tatto particolarmente scorrevole, caldo e ceroso, con buone resistenze sia ad umido che a secco. E' molto indicato oer svariati articoli, come arredamento pelletteria ed abbigliamento su bovine. I migliori risultati in termini di resistenze meccaniche si ottengono reticolando con poliaziridina.

### Main applications

TWC-1503 MATT is a ready-to-use top finish and it forms soft and matt films. It allows to obtain pleasant waxy and warm feel, with good dry and wet resistance. It is very suitable for several kind of articles, such as furniture, leather goods and gbovine garment. The best results are obtained by cross-linking with polyaziridine.

KEEP FROM FREEZING; CAN BE STORE FOR 6 MONTHS BETWEEN +5 AND +35°C.

Our application reccomandation are in line with our present state of knowledge and they do not exempt the customer from performing his own tests to determine the suitability of the supplied products for the intended purposes. Application of the products lies outside the scope of our control and therefore comes within the customer's sphere or responsibility. We guarantee the satisfactory quality of our products subject to general terms of sale and delivery.